



INTERNATIONAL STANDARD ISO/IEC 14496-4:2004

TECHNICAL CORRIGENDUM 2

Published 2007-04-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION  
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

## Information technology — Coding of audio-visual objects —

### Part 4: Conformance testing

#### TECHNICAL CORRIGENDUM 2

*Technologies de l'information — Codage des objets audiovisuels —*

*Partie 4: Essai de conformité*

*RECTIFICATIF TECHNIQUE 2*

Technical Corrigendum 2 to ISO/IEC 14496-4:2004 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

*In Clause 2, "Normative references", remove the following:*

"IEEE Standard Specifications for the Implementations of 8 by 8 Inverse Discrete Cosine Transform, IEEE Std 1180-1990, December 6, 1990"

---

ICS 35.040

Ref. No. ISO/IEC 14496-4:2004/Cor.2:2007(E)

© ISO/IEC 2007 – All rights reserved

Published in Switzerland

*In Clause 2, “Normative references”, add the following:*

“ISO/IEC 23002-1, *Information technology — MPEG video technologies — Part 1: Accuracy requirements for implementation of integer-output 8×8 inverse discrete cosine transform*”

*In 5.3, “Procedure for testing bitstream compliance”, replace*

“A verifier which does perform the IDCT transform and calculates the reconstructed samples must comply with all the arithmetic precision requirements specified in ISO/IEC 14496-2. In addition, the IDCT of such a verifier shall be an embodiment of the saturated mathematical integer-number IDCT specified in Annex A of ISO/IEC 14496-2 (a software implementation using 64-bit double-precision floating-point is sufficient).”

*with the following:*

“A verifier which does perform the IDCT transform and calculates the reconstructed samples must comply with all the arithmetic precision requirements specified in ISO/IEC 14496-2. In addition, the IDCT of such a verifier shall be an embodiment of the mathematical integer-number IDCT specified in Annex A of ISO/IEC 14496-2:2004 (a software implementation using 64-bit double-precision floating-point is sufficient).”

*In 5.4, “Definition of visual decoder compliance”, replace*

“The reference decoder is a decoder that implements precisely the decoding process as specified in ISO/IEC 14496-2. The IDCT function that shall be used when running the reference decoder is the very accurate approximation of the mathematical saturated integer-number IDCT specified in Annex A of ISO/IEC 14496-2 obtained by implementing IDCT with double-precision arithmetic.”

*with the following:*

“The reference decoder is a decoder that implements precisely the decoding process as specified in ISO/IEC 14496-2. The IDCT function that is used when running the reference decoder shall be an embodiment of the mathematical integer-number IDCT specified in Annex A of ISO/IEC 14496-2:2004 (a software implementation using 64-bit double-precision floating-point is sufficient).”

*Replace the content of 5.4.2, “Requirement on arithmetic accuracy in video objects (with IDCT)”, with the following:*

“When a bitstream contains some 8×8 blocks with non-zero DCT coefficients, the output of a compliant decoder may differ from the output of the reference decoder. However, because of the accuracy requirements on the IDCT implementation used by the decoder, there exist some accuracy requirements on the output of a compliant ISO/IEC 14496-2 video decoder.

The IDCT implementation used in a compliant decoder shall meet all the requirements defined in Annex A of ISO/IEC 14496-2:2004, including all tests specified therein.”

*In 5.5.3, “Specification of the test bitstreams”, replace*

“All the bitstreams in the test suite must be such that the output of the non-saturated integer number mathematical IDCT, as defined in Annex A of ISO/IEC 14496-2, has values within the range [-384, 383] for each coded block.”

*with the following:*

“All the bitstreams in the test suite must be such that the output of the mathematical integer-number IDCT, as defined in Annex A of ISO/IEC 14496-2:2004, has values within the range [-384, 383] for each coded block.”