

INTERNATIONAL
STANDARD

ISO
11266

First edition
1994-09-15

**Soil quality — Guidance on laboratory
testing for biodegradation of organic
chemicals in soil under aerobic conditions**

*Qualité du sol — Guide relatif aux essais en laboratoire pour la
biodégradation de produits chimiques organiques dans le sol sous
conditions aérobiées*

STANDARDSISO.COM : Click to view the full PDF of ISO 11266:1994



Reference number
ISO 11266:1994(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11266 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 4, *Biological methods*.

Annexe A of this International Standard is for information only.

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

Organic chemicals may be introduced into the soil both intentionally and accidentally, after which they may, or may not, degrade biologically. For chemicals which do degrade, the rate of degradation can vary considerably, depending not only on the molecular structure of the chemical, but also on soil conditions such as temperature, water and oxygen availability which influence microbial activity. The activity of micro-organisms often plays a major role in degradative processes.

It is necessary to have laboratory tests available to estimate the rate and extent of biodegradation and thereby the persistence of organic chemicals in soil. Numerous laboratory methods are available for the estimation of aerobic biodegradation, but these differ considerably according to the specific circumstances, for example, soil type, temperature and incubation times.

This International Standard provides general guidelines for the selection and conduct of tests for determining the biodegradation of organic chemicals in aerobic soils.

At the time of writing, there is insufficient agreement on methodology for testing biodegradability in anaerobic soils for guidelines to be prepared.

STANDARDSISO.COM . Click to View the effect of ISO 11266:1994

This page intentionally left blank

STANDARDSISO.COM : Click to view the full PDF of ISO 11266:1994

Soil quality — Guidance on laboratory testing for biodegradation of organic chemicals in soil under aerobic conditions

1 Scope

This International Standard provides guidance on the selection and conduct of appropriate test methods for the determination of biodegradation of organic chemicals in aerobic soils. It does not describe any specific test method.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 9408:1991, *Water quality — Evaluation in an aqueous medium of the "ultimate" aerobic biodegradability of organic compounds — Method by determining the oxygen demand in a closed respirometer*.

ISO 10381-6:1993, *Soil quality — Sampling — Guidance on the collection, handling and storage of soil for the assessment of aerobic microbial processes in the laboratory*.

ISO 10390:1994, *Soil quality — Determination of pH*.

ISO 10694:—¹⁾, *Soil quality — Determination of organic and total carbon after dry combustion ("Element analysis")*.

ISO 11260:1994, *Soil quality — Determination of cation exchange capacity and base saturation — Method using barium chloride solution*.

ISO 11261:—¹⁾, *Soil quality — Determination of total nitrogen — Kjeldahl method using titanium dioxide as catalyst*.

ISO 11274:—¹⁾, *Soil quality — Determination of the water retention characteristic — Laboratory methods*.

ISO 11277:—¹⁾, *Soil quality — Determination of particle size distribution*.

ISO 11461:—¹⁾, *Soil quality — Determination of soil water content calculated on a volume basis — Gravimetric method*.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 biodegradation: The molecular degradation of an organic substance resulting from the complex actions of living organisms.

3.2 primary biodegradation: The degradation of a substance to an extent sufficient to remove some characteristic property of the parent molecule. In practice, this will be determined by analysis as a loss of parent compound or some specific function of the parent compound.

3.3. ultimate biodegradation: The breakdown of an organic compound to carbon dioxide, water, the oxides or mineral salts of any other elements present, and products associated with the normal metabolic processes of microorganisms.

3.4 persistence: The residence time of a chemical species in a specifically defined compartment of the environment.

3.5 the disappearance time DT-50: The time taken for the concentration of a given compound to decrease by 50 % of its original value.

1) To be published.

3.6 the disappearance time DT-90: The time taken for the concentration of a given compound to decrease by 90 % of its original value.

3.7 bound residues; non-extractable residues: Chemical species in plants and soils, originating from, for example, organic molecules that are not extracted by methods which do not significantly change the chemical nature of these residues. These non-extractable residues are considered to exclude fragments recycled through metabolic pathways leading to natural products. (For examples and further information, see [3] in annex A.)

3.8 mineralization: The complete degradation of an organic substance to inorganic products.

4 Principle

After addition of the test compound to a selected soil (5.1), biodegradation is measured under aerobic conditions (see ISO 9408). Use of a radiolabelled compound allows determination of the rate of disappearance of the test compound and the formation of metabolites, carbon dioxide, other volatiles and non-extractable residue. The metabolites should be identified using appropriate analytical methods. The disappearance of the test compound can also be followed by specific analysis.

5 Materials

5.1 Soil

If practicable, soils selected for testing should come directly from the site where chemical contact is anticipated. However, if it is not possible to obtain clean samples owing to contamination which has already been introduced, the soil selected should have comparable properties.

The field history of the soil used should be considered and recent amendments, such as tillage practices and pesticide applications, noted. Precise data should be provided on the sampling site, its location, the presence of plants or previous crops, the date of removal of the sample from the field, and the sampling depth.

5.1.1 Soil characteristics

A knowledge of soil characteristics is essential for full interpretation of the results of the study. It is therefore recommended that at least the following tests are performed on the selected soil.

a) Physical properties:

- 1) particle size analysis in accordance with ISO 11277;

2) field water content in accordance with ISO 11461;

3) total water holding capacity and/or water retention characteristic in accordance with ISO 11274.

b) Chemical properties:

- 1) pH of the soil in accordance with ISO 10390, or the pH in KCl solution or CaCl_2 solution;
- 2) organic matter content in accordance with ISO 10694;
- 3) cation exchange capacity (CEC) in accordance with ISO 11260;
- 4) nitrogen content in accordance with ISO 11261.

c) Biological properties:

The microbial activity should be determined by either using an appropriate biodegradable reference compound or by determining active biomass in accordance with an International Standard which will be published later.

NOTE 1 It may be useful to determine the microbial activity before conducting a biodegradation test, and to determine whether any changes in microbial activity have occurred during the test.

5.2 Test material

Ideally, substances to be tested should be pure compounds (chemical purity > 98 %). The influence of any carriers or formulation ingredients should also be considered.

The following data on compounds are important for the interpretation of results:

- name (IUPAC);
- structure;
- relative molecular mass;
- data on purity;
- stability in water and in organic solvents;
- solubility in water;
- vapour pressure;
- octanol/water partition coefficient;
- sorption constant;
- acid dissociation constant;
- for radiolabelled chemicals:
 - the nature and position of the label,
 - specific activity,
 - radiochemical purity.

NOTE 2 The results of studies using radiolabelled materials depends on the position of the radiolabel. The label should thus be positioned in such a way that the transformation process may be followed as far as possible.

6 Collection, handling and storage of soil

It is important that ISO 10381-6 is followed to ensure that viability of soil microorganisms is maximized during sampling.

7 Procedure

7.1 Addition of test substance

The concentration to be used in the test depends on the experimental objectives. The test chemical may be added in a number of ways:

- a) in water (depending on the solubility in water);
- b) in organic solvents (depending on the solubility in the solvent). The amount of solvent used should be kept to the minimum necessary for the application of the compound. The possible toxicity and biodegradability of the solvent should be taken into account;
- c) directly as a solid, for example mixed in quartz sand.

Care should be taken to avoid adding test material at toxic levels. Compounds which are toxic, or have inhibitory effects on soil microorganisms at the applied concentration, will interfere with the determination of biodegradability. Also, if the substance is added in water, care should be taken to avoid over-wetting or compacting the soil.

7.2 Incubation

The treated soil is divided into aliquots of at least 50 g (dry mass equivalent) and placed in incubation flasks. Generally at least two replicates per sampling point should be incubated. However, increasing the number of replicates increases the precision of the test.

When using unlabelled test material, controls should be run simultaneously. The controls should contain soil plus the amount of water or solvent which was used for the application of the test material in the treated replicates.

7.2.1 Incubation system

The incubation system to be used will depend on the method(s) of analysis and measurement. A number of

systems are available and some of them are listed in [1] and [2] in annex A. The incubation system used should ensure that sufficient oxygen is present to maintain aerobic conditions. If it is necessary to distinguish between biological and other degradation or dissipation processes, a sterile incubation should be performed.

If the evaluation of carbon dioxide is used to follow the degradation process, care should be taken when using alkaline soils. These soils may absorb carbon dioxide, resulting in an underestimation of carbon dioxide production.

If mineralization measurements are carried out with a non-radiolabelled compound, attention should be given to the mineralization rate of the control, and possible production of carbon dioxide from inorganic carbonates.

NOTE 3 A number of systems are described in [1] and [2] in annex A.

7.2.2 Incubation conditions

7.2.2.1 Illumination

The incubation is usually carried out in the dark to avoid algal growth on the soil surface. However, if the contribution of algae to biodegradation needs to be considered, appropriate lighting conditions should be selected. Under such conditions, the contribution to degradation by photolysis may be significant and should be taken into account.

7.2.2.2 Temperature

The incubation temperature should be selected according to the specific goals of the study. In general, maximum microbial activity in soil is found between 25 °C and 35 °C. However, for soils from temperate zones, a temperature between 10 °C and 25 °C is adequate and more representative of natural conditions. The minimum and maximum temperatures to which the incubation system is exposed should be measured and recorded at regular intervals throughout the incubation and should not vary by more than ± 2 °C.

7.2.2.3 Water content

The water content of the soil should be appropriate for the specific goals of the study. It should be determined at the start of the test and monitored during incubation by weighing. Any water lost should be replaced with an appropriate amount of deionized or distilled water. The original water content should be maintained to within ± 5 %.

Water content is most appropriately expressed as pore-water pressure. Generally, microbial activity in

soil is optimal at between $-0,01$ MPa and $-0,031$ MPa and decreases as the soil becomes either waterlogged (pore-water pressure near zero) or excessively dry, with large, negative pore-water pressures.

Pore-water pressures should be determined in accordance with ISO 11274.

Alternatively, waterholding capacity (WHC) may be used, but this is not recommended as it does not give comparable measurements between different soil samples. Maximum microbial activity is normally found at between 40 % and 60 % of the maximum WHC of a given soil, although a WHC of as high as 75 % can be used for special purposes.

NOTE 4 For further information, consult [4] in annex A.

7.2.3 Test duration

There is no recommended minimum length for a test but, as microbial activity in soil decreases during long incubation periods, it is recommended that tests should not be continued for longer than 120 d.

7.2.4 Sampling

Samples should be taken at regular intervals during the incubation period, depending on the duration of the test and the rate of biodegradation of the test material. At least five sampling points are required to establish a degradation curve. As many materials degrade more rapidly during the early stages of incubation, the following sampling frequency is recommended: 0 d, 2 d, 4 d, 8 d, 16 d, 32 d, 64 d and 120 d after application. For destructive sampling methods, for example direct analysis of the soil, it is recommended that the entire contents of an individual incubation flask are sampled.

7.3 Analysis

The type of analysis will depend on the aims of the study and whether primary and/or ultimate biodegradation data are required.

The analyses chosen to monitor the degradation process are dependent on the chemical itself and whether or not a radiolabelled compound has been used.

In general, the following analyses should be considered.

- a) For primary degradation (unlabelled substances):
 - loss of parent compound.

- b) For ultimate degradation (unlabelled substances):
 - determination of oxygen consumption and/or carbon dioxide production;
 - loss of parent compound.
- c) For metabolism (labelled substances):
 - determination of labelled carbon dioxide production;
 - determination of volatile compounds, both parent compound and metabolites;
 - determination of extractable water or solvents;
 - determination of non-extractable bound residues.

For the determination of extractable materials, solvents which do not alter the parent compound or its metabolites should be used. Care should be taken to follow extraction procedures which will remove as much of the extractable material as possible. The analysis of metabolites and parent compound may be performed using thin layer chromatography (TLC), high performance liquid chromatography (HPLC), gas chromatography (GC), mass spectrometry (MS) or spectrophotometric measurements.

8 Expression of results

All data should be presented in a tabular and graphic form (degradation curve).

DT-50 and DT-90 values should be calculated using, for example, the models described in [6] in annex A.

Additional useful information includes the determination of volatile compounds, formation and persistence of metabolites, and non-extractable residues.

NOTES

5 If no biodegradation is observed, the likely reasons may be:

- a) the test substance is toxic;
- b) the test substance does not biodegrade;
- c) the microbial activity of the soil is zero.

6 To assist in the evaluation of results, see for example [5] in annex A.

9 Test report

The test report on the degradation of the test compound should include the following information:

- a) a reference to this International Standard;
- b) data on the test chemical used, see 5.2;

- c) data on the soils used, see 5.1;
- d) data on the test procedure, test method used, concentrations used, methods of application, data on the performance of the test, sampling data, etc., see clause 7;
- e) data on the analytical methods used, for example, detection limits, quality control procedures, reference substances analysed;
- f) raw data figures on the results of the analyses;
- g) evaluation and conclusions of the evaluation.

STANDARDSISO.COM : Click to view the full PDF of ISO 11266:1994