

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

**ISO RECOMMENDATION
R 571**

METAL REEDS WITH DOUBLE-SPRING BAULK

1st EDITION

April 1967

COPYRIGHT RESERVED

STANDARDSISO.COM : Click to view the full PDF of ISO/R 571:1967

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 571, *Metal Reeds with Double-spring Baulk*, was drawn up by Technical Committee ISO/TC 72, *Textile Machinery and Accessories*, the Secretariat of which is held by l'Association Suisse de Normalisation (SNV).

Work on this question by the Technical Committee began in 1959 and led, in 1963, to the adoption of a Draft ISO Recommendation.


In September 1964, this Draft ISO Recommendation (No. 708) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies:

Chile	India	Turkey
Czechoslovakia	Netherlands	U.A.R.
France	Poland	United Kingdom
Germany	Spain	
Greece	Switzerland	

One Member Body opposed the approval of the Draft: U.S.S.R.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in April 1967, to accept it as an ISO RECOMMENDATION.

METAL REEDS WITH DOUBLE-SPRING BAULK



* Minimum depth = $h - 5d$

b = Width of dents

d = Thickness of reed baulk

h = Overall depth

Basic dimensions				Co-ordinated dimensions							
h	d	b		b	mm	2.5	3	4	5	6	
				mm	in	0.10	0.12	0.16	0.20	0.24	
110	4.33	6	0.24	2.5	0.10						
120	4.72	6.5	0.26	3	0.12	6	6.5	8	9	10	
130	5.12	8	0.31	4	0.16	0.24	0.26	0.31	0.35	0.39	
140	5.51	9	0.35	5	0.20	110	4.33	X	X	X	X
150	5.91					120	4.72	X	X	X	X
160	6.30	10	0.39	6	0.24	130	5.12	X	X	X	X
						140	5.51		X	X	X
						150	5.91		X	X	X
						160	6.30		X	X	X