

AEROSPACE MATERIAL SPECIFICATION

Submitted for recognition as an American National Standard



AMS 3138/5B

Issued OCT 1980
Revised JAN 1999

Superseding AMS 3138/5A

(R)

Coating Material, Fluorocarbon (FKM) Elastomeric Anti-Static Topcoating, White

1. SCOPE:

1.1 Form:

This specification covers a fluorocarbon (FKM) elastomeric coating material for fiber-reinforced-resin composite structures in the form of a two-component, brushable or sprayable liquid.

1.2 Application:

Primarily as a topcoating over AMS 3138/1, AMS 3138/2, or AMS 3138/3 base coating for protection of aircraft and missile radomes and other components from static.

2. APPLICABLE DOCUMENTS:

See AMS 3138.

3. TECHNICAL REQUIREMENTS:

3.1 Basic Specification:

The complete requirements for procuring the coating material described herein shall consist of this document and the latest issue of the basic specification, AMS 3138.

3.2 Material:

Shall be as specified in AMS 3138.

3.2.1 Color: Shall be white and of sufficient intensity to hide completely the surface of the substrate when applied at the specified coating thickness.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright 1999 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in U.S.A.

QUESTIONS REGARDING THIS DOCUMENT:
TO PLACE A DOCUMENT ORDER:
SAE WEB ADDRESS:

(724) 772-7154
(724) 776-4970
<http://www.sae.org>

FAX: (724) 776-0243
FAX: (724) 776-0790