

REV. D

AS3246

FEDERAL SUPPLY CLASS
5306

RATIONALE

THIS IS A LIMITED SCOPE CHANGE. RESTORE DIMENSION FOR MINIMUM BEARING SURFACE IN FIGURE 1 TO PREVIOUS REVISION (CORRECTING A TYPOGRAPHICAL ERROR INTRODUCED IN REV. C).

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE invites your written comments and suggestions. SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled.





FIGURE 1 - BOLT

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS3246D>



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7466



AEROSPACE STANDARD

BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, NICKEL ALLOY, UNS N07718, 185 KSI MIN, .3750-24 UNJF-3A

AS3246
SHEET 1 OF 3

REV. D

ISSUED 1980-07 REAFFIRMED 2007-06 REVISED 2015-02

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100	PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100
AS3246-03	.552- .572	.025	.108	3.06	AS3246-33	2.865-2.885	1.732	1.875	9.61
AS3246-04	.615- .635	.025	.108	3.24	AS3246-34	2.990-3.010	1.857	2.000	9.97
AS3246-05	.678- .698	.025	.108	3.42	AS3246-35	3.115-3.135	1.982	2.125	10.32
AS3246-06	.740- .760	.025	.108	3.59	AS3246-36	3.240-3.260	2.107	2.250	10.67
AS3246-07	.802- .822	.025	.108	3.77	AS3246-37	3.365-3.385	2.232	2.375	11.03
AS3246-08	.865- .885	.025	.108	3.94	AS3246-38	3.490-3.510	2.357	2.500	11.39
AS3246-09	.928- .948	.025	.108	4.12	AS3246-39	3.615-3.635	2.482	2.625	11.74
AS3246-10	.990-1.010	.025	.108	4.30	AS3246-40	3.740-3.760	2.607	2.750	12.09
AS3246-11	1.052-1.072	.025	.108	4.47	AS3246-41	3.865-3.885	2.732	2.875	12.45
AS3246-12	1.115-1.135	.025	.125	4.65	AS3246-42	3.990-4.010	2.857	3.000	12.80
AS3246-13	1.178-1.198	.045	.188	4.83	AS3246-43	4.115-4.135	2.982	3.125	13.15
AS3246-14	1.240-1.260	.107	.250	5.00	AS3246-44	4.240-4.260	3.107	3.250	13.50
AS3246-15	1.302-1.322	.169	.312	5.19	AS3246-45	4.365-4.385	3.232	3.375	14.87
AS3246-16	1.365-1.385	.232	.375	5.37	AS3246-46	4.490-4.510	3.357	3.500	14.22
AS3246-17	1.428-1.448	.295	.438	5.54	AS3246-47	4.615-4.635	3.482	3.625	14.57
AS3246-18	1.490-1.510	.357	.500	5.72	AS3246-48	4.740-4.760	3.607	3.750	14.93
AS3246-19	1.552-1.572	.419	.562	5.90	AS3246-49	4.865-4.885	3.732	3.875	15.28
AS3246-20	1.615-1.635	.482	.625	6.07	AS3246-50	4.990-5.010	3.857	4.000	15.63
AS3246-21	1.678-1.698	.545	.688	6.25	AS3246-51	5.115-5.135	3.982	4.125	15.99
AS3246-22	1.740-1.760	.607	.750	6.43	AS3246-52	5.240-5.260	4.107	4.250	16.34
AS3246-23	1.802-1.822	.669	.812	6.60	AS3246-53	5.365-5.385	4.232	4.375	16.70
AS3246-24	1.865-1.885	.732	.875	6.78	AS3246-54	5.490-5.510	4.357	4.500	17.05
AS3246-25	1.928-1.948	.795	.938	6.96	AS3246-55	5.615-5.635	4.482	4.625	17.39
AS3246-26	1.990-2.010	.857	1.000	7.13	AS3246-56	5.740-5.760	4.607	4.750	17.73
AS3246-27	2.115-2.135	.982	1.125	7.48	AS3246-57	5.865-5.885	4.732	4.875	18.07
AS3246-28	2.240-2.260	1.107	1.250	7.84	AS3246-58	5.990-6.010	4.857	5.000	18.41
AS3246-29	2.365-2.385	1.232	1.375	8.20					
AS3246-30	2.490-2.510	1.357	1.500	8.55					
AS3246-31	2.615-2.635	1.482	1.625	8.91					
AS3246-32	2.740-2.760	1.607	1.750	9.26					

NOTES:

- FOR PART NUMBERS AS3246-03 THRU AS3246-21 THE THREAD PD (DATUM **Z**) SHALL REPLACE DATUM **Y**.
- MATERIAL: CORROSION AND HEAT RESISTANT NICKEL ALLOY PER AMS5662 (UNS N07718).
- PROCUREMENT SPECIFICATION: AS7466.
- FLUORESCENT PENETRANT INSPECTION PER ASTM E1417/E1417M, TYPE 1, SENSITIVITY LEVEL 2.
- SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICRINCHES Ra.
- BREAK SHARP EDGES .003 TO .015 UNLESS OTHERWISE SPECIFIED.
- DIMENSIONS IN INCHES.

	AEROSPACE STANDARD	AS3246 SHEET 2 OF 3	REV. D
	BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, NICKEL ALLOY, UNS N07718, 185 KSI MIN, .3750-24 UNJF-3A		