

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

REV.
A

SAE AS39029/45


RATIONALE

REVISE TO INCLUDE COMMENTS RECEIVED BY THE GOVERNMENT AND INDUSTRY SINCE 1988, INCORPORATES VARIOUS AMENDMENTS, REMOVE GOVERNMENT JARGON AS A RESULT OF THE WORD-FOR-WORD TRANSFERENCE OF AS39029 TO SAE, UPDATE SPECIFICATION REFERENCES, ALIGN SPECIFICATIONS WITH SAE GUIDELINES AS NEEDED, AND REVIEW SPECIFICATIONS FOR KNOWN TECHNICAL PROBLEMS.


NOTICE

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF: SAE AS39029.


FEDERAL SUPPLY CLASS
5999



SOCKET INTERFACE DESIGN FOR ALL BIN CODES
WIRE BARREL DESIGN FOR BIN CODES 295 THRU 297 (SIZES 16 AND 12 CONTACTS)



WIRE BARREL DESIGN
BIN CODE 294 (16-22)




WIRE BARREL DESIGN
BIN CODES 298-300 (SIZES 8, 4, 0)

FIGURE 1 - SOCKET CONTACT

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS39029/45a>

THIRD ANGLE PROJECTION



CUSTODIAN: SAE AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS39029

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

(R) CONTACTS, ELECTRICAL CONNECTOR,
SOCKET, CRIMP REMOVABLE (FOR MIL-DTL-
5015 SERIES MS3400 CONNECTORS)

SAE AS39029/45
SHEET 1 OF 4

**REV.
A**

Copyright 2008 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2001-03 REVISED 2008-10

TABLE 1 - CONTACT DIMENSIONS

BIN Code	E Dia	F Dia	J Dia	M Ref	N Dia	P Dia	R	S	T Min	U Min	W	A	B	C	D Dia	G Dia	K	L
294	0.0355 0.0335	0.148 (3.76) 0.133 (3.38)	0.113 0.110	1.272	0.064	0.087 0.083	0.189 0.185	0.808 0.798	0.510	0.086	53 43	0.285 0.280	0.106 0.100	0.042 0.036	0.032 0.026	0.078 0.076	0.216 0.206	0.067 0.061
295	0.068			1.286								0.298	0.079	0.048	0.042	0.105	0.281	0.090
296		0.202	0.161		0.0955	0.135			0.625	0.125						0.153 0.147		0.125 0.115
297	0.102 0.098																	
298	0.184 0.179	0.313 (7.95) 0.309 (7.85)	0.252 0.249	1.505 (38.23)	0.149 0.145	0.225 0.221				0.193	31 29	0.520 0.510	0.094 0.084		0.066 0.060	0.269 0.263	0.534 0.480	0.230 0.220
299	0.286 0.279	0.419 (10.64) 0.409 (10.39)	0.336 0.333		0.232 0.228	0.310 0.307	0.253 0.249	0.744 0.734		0.280						0.380 0.370		0.364 0.354
300	0.458 0.451	0.611 (15.52) 0.601 (15.27)	0.518 0.515	1.660 (42.16)	0.364 0.360	0.492 0.489				0.386		0.675 0.665				0.568 0.558	0.690 0.636	0.542 0.532

TABLE 2 - MARKING AND DESIGN CHARACTERISTICS

BIN Codes	Color Bands			Mating End	Wire Barrel	Type Size	Class
	1st	2nd	3rd				
294	Red	White	Yellow	16	22	A	B
295	Red	White	Green	16	16		
296 1/	Red	White	Blue	12	16		
297	Red	White	Violet	12	12		
298	Red	White	Gray	8	8		
299	Red	White	White	4	4		
300	Orange	Black	Black	0	0		

1/ BIN 296 SHALL MEET ALL APPLICABLE TEST REQUIREMENTS FOR SIZE 12-14

TABLE 3 - TOOL REQUIREMENTS

BIN CODE	BASIC CRIMPING TOOL	DIE SET	LOCATOR	POSITIONER	INSTALLING TOOL	REMOVAL TOOL
294 1/	M22520/1-01	---	---	M22520/1-02 BLUE	M81969/17-09	M81969/19-01
295	M22520/1-01	---	---	M22520/1-02 BLUE	M81969/17-04	M81969/19-01
296	M22520/1-01	---	---	M22520/1-02 YELLOW	M81969/17-04	M81969/19-02
297	M22520/1-01	---	---	M22520/1-02 YELLOW	M81969/17-05	M81969/19-02
298	M22520/23-01	M22520/23-02	M22520/23-09	---	M81969/17-06	M81969/19-03
299	M22520/23-01	M22520/23-04	M22520/23-11	---	M81969/17-07	M81969/19-04
300	M22520/23-01	M22520/23-05	M22520/23-13	---	M81969/17-08	M81969/19-05

1/ USED SELECTOR NUMBER 3, 2, 1 FOR WIRE SIZE 22, 24, 26 RESPECTIVELY.

TABLE 4 - PART NUMBERS

AS39029 PART NUMBER	BIN CODE	SUPERSEDED PART NUMBER(S)
M39029/45-294	294	MS90454-16-22
M39029/45-295	295	MS90454-16-16
M39029/45-296	296	MS90454-12-16
M39029/45-297	297	MS90454-12-12
M39029/45-298	298	MS90454-8-8
M39029/45-299	299	MS90454-4-4
M39029/45-300	300	MS90454-0-0

DETAIL SPECIFICATION REQUIREMENTS:

1. DESIGN:

CONTACT SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1, TABLE 1 AND 2. DIMENSIONS ARE IN INCHES AND SHOWN AFTER PLATING. UNLESS OTHERWISE SPECIFIED, SPHERICAL END DIMENSIONS SHALL CONFORM TO AS39029. ALL DIMENSIONS IN PARENTHESES ARE METRIC EQUIVALENTS AND PROVIDED FOR GENERAL INFORMATION ONLY (SEE AS39029 SECTION 6).

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLE 3.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 4. SUPERSEDED PART NUMBERS ARE AS SPECIFIED.